

TRACTOR SPECIFICATIONS			
ENGINE			
Type		Diesel, 3-cylinder, water cooled, 6-valve, mechanical indirect injection	
Power output	KM	16 (acc. to SAE), 14 (acc. to ECE-R24)	
Total displacement	cm3	719	
PTO power	KM	12.5	
Max torque	Nm	40.5	
Fuel tank capacity	L	14	
TRANSMISSION			
Transmission type		Mechanically engaged 4x4	
Gearbox		Mechanical	
Total number of speeds		F6/R2	
Max speed	km/h	19 (depending on tire size)	
Gearbox		3 forward speeds + reverse gear	
Reduction box		2 speed	
Shuttle		N/A	
Main clutch		Dry, one stage	
Brakes		Mechanical, wet disc brakes	
Rear differential lock		Mechanical	
PTO			
Rear PTO speeds		540 / 1000	
Rear PTO clutch		N/A	
Mid-mounted PTO speeds		2500	
HYDRAULICS			
Hydraulic pump capacity	L/min	14.1	
3-point linkage category		I	
3-point linkage control		Mechanical: position control	
Lifting capacity	kg	540	
External hydraulic outlets (pairs)		1 (one-way flow)	
DIMENSIONS AND WEIGHT			
Total length	mm	2360	
Total height	mm	1223	
Total width	mm	940 (min. thread)	
Wheelbase	mm	1270	
Thread	Front	mm	778
	Rear	mm	707-1035
Standard tire size		Front: 5-12; Rear:8-16	
Turning radius	m	1,8 (with braking)	
Tractor weight in standard spec.	kg	560	